

## Features

- Low  $V_{CE(sat)}$
- Fast Switching
- High Ruggedness
- Short-Circuit Rated




## Product Summary


$V_{CES}$	1200V
$I_C$	150A
$V_{CE(sat),typ}$	1.6V

## Applications

- General Purpose Inverters
- Frequency Converters
- Industrial Motor Drives
- Uninterruptible Power Supply (UPS)
- Servos



## Internal Connection



## • IGBT, Inverter

### Absolute Maximum Ratings

Parameter	Symbol	Limit	Unit
Collector-to-Emitter Voltage	$V_{CES}$	1200	V
Gate-to-Emitter Voltage	$V_{GES}$	$\pm 20$	
Transient Gate-emitter Voltage ( $t_p \leq 10\mu s$ , $D < 0.010$ )		$\pm 30$	
Continuous DC Collector Current ( $T_c = 100^\circ C$ , $T_J = 175^\circ C$ )	$I_{CDC}$	150	A
Repetitive Peak Collector Current ( $t_p = 1ms$ )	$I_{CRM}$	300	
Maximum Power Dissipation ( $T_c = 25^\circ C$ , $T_J = 175^\circ C$ )	$P_{D(max)}$	735	W

**Electrical Characteristics** <sup>(1), (2)</sup>

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector-to-Emitter Breakdown Voltage	$BV_{CES}$	$V_{GE} = 0V, I_C = 250\mu A$	1200	-	-	V
Collector-to-Emitter Leakage Current	$I_{CES}$	$V_{CE} = 1200V, V_{GE} = 0V$	-	-	5	mA
Gate-to-Emitter Leakage Current	$I_{GES}$	$V_{CE} = 0V, V_{GE} = \pm 20V$	-	-	400	nA
Gate Threshold Voltage	$V_{GE(th)}$	$V_{CE} = V_{GE}, I_C = 1.5mA$	4.8	6	7.2	V
Collector-to-Emitter Saturation Voltage	$V_{CE(sat)}$	$V_{GE} = 15V, I_C = 150A$	-	1.6	2.0	
		$V_{GE} = 15V, I_C = 150A, T_J = 150^\circ C$	-	1.95	-	
		$V_{GE} = 15V, I_C = 150A, T_J = 175^\circ C$	-	2.05	-	
Total Gate Charge	$Q_g$	$V_{CC} = 600V, V_{GE} = \pm 15V, I_C = 150A$	-	1.44	-	$\mu C$
Internal Gate Resistance	$R_{Gint}$	-	-	3	-	$\Omega$
Input Capacitance	$C_{iss}$	$V_{CE} = 25V, V_{GE} = 0V, f = 1MHz$	-	9.73	-	nF
Output Capacitance	$C_{oss}$		-	0.68	-	
Reverse Transfer Capacitance	$C_{rss}$		-	0.13	-	
Turn-on Delay time	$t_{d(ON)}$	$V_{CC} = 600V, V_{GE} = \pm 15V, R_G = 5.1\Omega, I_C = 150A, L_{load} = 0.82mH, \text{Energy losses include "tail" and diode reverse recovery.}$	-	358	-	ns
Rise Time	$t_r$		-	48	-	
Turn-off Delay time	$t_{d(OFF)}$		-	452	-	
Fall Time	$t_f$		-	154	-	
Turn-On Switching Loss	$E_{on}$		-	8.5	-	mJ
Turn-Off Switching Loss	$E_{off}$		-	10.0	-	
IGBT Total Switching Loss	$E_{ts}$		-	18.5	-	
Turn-on Delay time	$t_{d(ON)}$	$V_{CC} = 600V, V_{GE} = \pm 15V, R_G = 5.1\Omega, I_C = 150A, L_{load} = 0.82mH, \text{Energy losses include "tail" and diode reverse recovery. } T_J = 150^\circ C$	-	632	-	ns
Rise Time	$t_r$		-	60	-	
Turn-off Delay time	$t_{d(OFF)}$		-	470	-	
Fall Time	$t_f$		-	278	-	
Turn-On Switching Loss	$E_{on}$		-	14.2	-	mJ
Turn-Off Switching Loss	$E_{off}$		-	16.8	-	
IGBT Total Switching Loss	$E_{ts}$		-	31	-	
Short Circuit Collector Current	$I_{C(SC)}$	$V_{GE} = 15V, V_{CC} \leq 600V, t_{SC} \leq 10\mu s$	-	600	-	A

## • Diode, Inverter

### Absolute Maximum Ratings

Parameter	Symbol	Limit	Unit
Repetitive Peak Reverse Voltage	$V_{RRM}$	1200	V
Continuous DC Forward Current	$I_F$	150	A
Repetitive Peak Forward Current ( $t_P = 1ms$ )	$I_{FRM}$	300	

### Electrical Characteristics <sup>(1)</sup>

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Diode Forward Voltage	$V_F$	$I_F = 150A$	-	2.0	2.4	V
		$I_F = 150A$ $T_J = 150^{\circ}C$	-	1.8	-	
		$I_F = 150A$ $T_J = 175^{\circ}C$	-	1.75	-	
Diode Reverse-Recovery Charge	$Q_{rr}$	$V_R = 600V, I_F = 150A,$ $dI_F/dt = -1690 A/\mu s$	-	10.66	-	$\mu C$
Diode Peak Reverse-Recovery Current	$I_{rrm}$		-	99	-	A
Diode Reverse-Recovery Loss	$E_{rr}$		-	3.35	-	mJ

## • NTC thermistors

### Characteristics

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Rated Resistance	$R_{25}$	-	-	5.0	-	k $\Omega$
Deviation of R100	$\Delta R/R$	$T_C = 100^{\circ}C$ $R_{100} = 493\Omega$	-5	-	5	%
Power Dissipation	$P_{25}$	-	-	-	20.0	mW
B-value	$B_{25/50}$	$R_2 = R_{25} \exp [B_{25/50}(1/T_2 - 1/(298.15 K))]$	-	3375	-	K

## • Module

### Absolute Maximum Ratings

Parameter	Symbol	Limit	Unit
Maximum Junction Temperature	$T_J$	-40 to +175	$^{\circ}C$
Operating Junction Temperature	$T_{vj op}$	-40 to +150	
Storage Temperature	$T_{stg}$	-40 to +125	
Isolation Voltage (RMS, $f = 50 Hz$ , $t = 1 min$ )	$V_{iso}$	2.5	kV

### Characteristics

Parameter	Symbol	Min	Typ	Max	Unit
Material of Module Baseplate	-	-	Cu	-	-
Internal Isolation	-	-	Al <sub>2</sub> O <sub>3</sub>	-	-
Creepage Distance, Terminal to Terminal	-	-	10	-	mm
Clearance, Terminal to Terminal	-	-	7.5	-	mm
Stray Inductance, Module	L <sub>SCE</sub>	-	21	-	nH
Module Lead Resistance, Terminal to Chip	R <sub>CC'+EE'</sub>	-	1.8	-	mΩ
Junction-to-Case Thermal Resistance, per IGBT, Inverter	R <sub>θJC</sub>	-	0.17	-	°C/W
Junction-to-Case Thermal Resistance, per Diode, Inverter		-	0.26	-	
Case-to-Heatsink Thermal Resistance, per IGBT, Inverter	R <sub>θCH</sub>	-	0.09	-	°C/W
Case-to-Heatsink Thermal Resistance, per Diode, Inverter		-	0.16	-	
Case-to-Heatsink Thermal Resistance, per Module		-	0.01	-	
Mounting Torque for Module Mounting, Screw M5	M	3.0	-	6.0	Nm
Weight per Module	G	-	300	-	g

(1) T<sub>J</sub> = 25°C unless otherwise specified

(2) t<sub>r</sub>: from 10% of I<sub>C</sub> to 90% of I<sub>C</sub>; t<sub>f</sub>: from 90% of I<sub>C</sub> to 10% of I<sub>C</sub>;

E<sub>on</sub>: from 10% of V<sub>GE</sub> to 10% of V<sub>CE</sub>; E<sub>off</sub>: from 90% of V<sub>GE</sub> to 10% of I<sub>C</sub>.

• **Typical Electrical Characteristics**




Fig. 1 IGBT (Inverter) Output Characteristics




Fig. 2 IGBT (Inverter) Transfer Characteristics



Fig. 3 RBSOA







Fig. 4 IGBT Switching Loss VS.  $I_C$   
( $V_{CC} = 600\text{V}$ ,  $V_{GE} = \pm 15\text{V}$ ,  $R_G = 5.1\Omega$ )




**Fig. 5 IGBT Switching Loss VS.  $R_G$**   
( $V_{CC} = 600V$ ,  $V_{GE} = \pm 15V$ ,  $I_C = 150A$ )




**Fig. 6 IGBT (Inverter) Transient Thermal Impedance**




**Fig. 7 Diode (Inverter) Forward Characteristics**




**Fig. 8 Diode (Inverter) Switching Loss vs.  $I_F$**   
( $V_{CC} = 600V$ ,  $R_G = 5.1\Omega$ )



**Fig. 9 Diode (Inverter) Switching Loss vs.  $R_G$**   
( $V_{CC} = 600V$ ,  $I_F = 150A$ )



**Fig. 10 Diode (Inverter) Transient Thermal Impedance**



**Fig. 11 NTC Temperature Characteristics**

30,31,32

16,17,18

1

2

27,28,29

3

4

33,34,35

5

6

24,25,26

7

8

9

10

21,22,23

11

12

13,14,15

Technical drawing of a rectangular metal plate with dimensions and tolerances. The drawing includes a top view, a side view, and a detail view of a corner.

**Top View Dimensions:**

- Overall width:  $122.7 \pm 0.5$
- Overall height:  $62.5 \pm 0.5$
- Inner width:  $110 \pm 0.2$
- Inner height:  $50 \pm 0.2$
- Distance from inner corner to outer corner (horizontal):  $11.76 \pm 0.2$
- Distance from inner corner to outer corner (vertical):  $11.76 \pm 0.2$
- Distance from center to outer corner (horizontal):  $54.21$
- Distance from center to outer corner (vertical):  $54.21$
- Distance from center to outer corner (horizontal):  $38.34$
- Distance from center to outer corner (vertical):  $34.53$
- Distance from center to outer corner (horizontal):  $30.72$
- Distance from center to outer corner (vertical):  $19.29$
- Distance from center to outer corner (horizontal):  $15.48$
- Distance from center to outer corner (vertical):  $11.67$
- Distance from center to outer corner (horizontal):  $0$
- Distance from center to outer corner (vertical):  $4.21$
- Distance from center to outer corner (horizontal):  $4.05$
- Distance from center to outer corner (vertical):  $0$
- Distance from center to outer corner (horizontal):  $15$
- Distance from center to outer corner (vertical):  $18.81$
- Distance from center to outer corner (horizontal):  $30.24$
- Distance from center to outer corner (vertical):  $34.05$
- Distance from center to outer corner (horizontal):  $45.48$
- Distance from center to outer corner (vertical):  $49.29$
- Distance from center to outer corner (horizontal):  $60.72$
- Distance from center to outer corner (vertical):  $64.53$
- Distance from center to outer corner (horizontal):  $75.95$
- Distance from center to outer corner (vertical):  $79.77$
- Distance from center to outer corner (horizontal):  $91.20$
- Distance from center to outer corner (vertical):  $95$
- Distance from center to outer corner (horizontal):  $114.05$

**Side View Dimensions:**

- Overall height:  $1.15 \pm 0.05$
- Distance from top surface to bottom surface:  $3.9 \pm 0.5$
- Distance from top surface to bottom surface:  $6.5 \pm 0.5$
- Distance from top surface to bottom surface:  $17 \pm 0.5$

**Detail View Dimensions:**

- Overall width:  $4.5 \pm 0.2$
- Overall height:  $1.5 \pm 0.2$
- Distance from top surface to bottom surface:  $11 \pm 0.5$
- Distance from top surface to bottom surface:  $5 \pm 0.5$
- Distance from top surface to bottom surface:  $1.5 \pm 0.2$
- Distance from top surface to bottom surface:  $0.2 \pm 0.2$
- Distance from top surface to bottom surface:  $0.2 \pm 0.2$

**Tolerances:**

- $\pm 0.5$
- $\pm 0.2$
- $\pm 0.05$

**Notes:**

- $\ast$  = all dimensions with tolerance of  $\pm 0.5$



---

## Notice

**General** – This document contains information on a product under development. Information in this document is believed to be accurate and reliable. However, JSAB Technologies does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

**Right to make changes** – JSAB Technologies reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

**Suitability for use** – JSAB Technologies' products are not designed, authorized or warranted to be suitable for use in medical, military, aircraft, space or life support equipment, nor in applications where failure or malfunction of an JSAB Technologies product can reasonably be expected to result in personal injury, death or severe property or environmental damage. JSAB Technologies accepts no liability for inclusion and/or use of JSAB Technologies' products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

**Applications** – Applications that are described herein for any of these products are for illustrative purposes only. JSAB Technologies makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

**Limiting values** – Stress above one or more limiting values may cause permanent damage to the device. Limiting values are stress ratings only and operation of the device at these or any other conditions above those given in the Characteristics sections of this document is not implied. Exposure to limiting values for extended periods may affect device reliability.

**Terms and conditions of sale** – JSAB Technologies' products are sold subject to the general terms and conditions of commercial sale, including those pertaining to warranty, intellectual property rights infringement and limitation of liability, unless explicitly otherwise agreed to in writing by JSAB Technologies. In case of any inconsistency or conflict between information in this document and such terms and conditions, the latter will prevail.

**No offer to sell or license** – Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

**Export control** – This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from national authorities.

**Quick reference data** – The Quick reference data is an extract of the product data given in the Limiting values and Characteristics sections of this document, and as such is not complete, exhaustive or legally binding.