

## Dual N-Channel Enhancement Mode MOSFET

**Description**

WM02DN080C-YW uses advanced power trench technology that has been especially tailored to minimize the on-state resistance. This device is suitable for un-directional or bidirectional load switch, facilitated by its common-drain configuration.


$V_{(BR)DSS}(V)$	$I_D(A)$	$R_{DS(on)}TYP\text{ (m}\Omega\text{)}$
20	8	13.0 @ $V_{GS}=4.5V$
		13.5 @ $V_{GS}=4.0V$
		14.0 @ $V_{GS}=3.7V$
		15.0 @ $V_{GS}=3.1V$
		17.5 @ $V_{GS}=2.5V$

**Features**

- Super high dense cell for low  $R_{DS(ON)}$
- RoHS Compliant and Halogen-Free
- ESD protected: Class 2

**Applications**

- Battery protection
- Load switch

**Schematic & PIN Configuration ( $T_A=25^\circ C$ , unless otherwise noted)****Absolute Maximum Rating**

Parameter	Symbol	Value	Unit
Drain-Source Voltage	$V_{DS}$	20	V
Gate-Source Voltage	$V_{GS}$	$\pm 12$	V
Continuous Drain Current	$I_D$	8	A
		6.3	A
Pulsed Drain Current <sup>1</sup>	$I_{DM}$	49	A
Single Pulse Avalanche Energy <sup>2</sup>	$E_{AS}$	18	mJ
Total Power Dissipation	$P_D$	1.56	W
Operating Junction and Storage Temperature Range	$T_J, T_{STG}$	-55 to 150	°C

**Thermal Characteristics**

Parameter	Symbol	Value	Unit
Thermal Resistance from Junction-to-Ambient <sup>3</sup>	$R_{\theta JA}$	80	°C/W


**Electrical Characteristics (T<sub>J</sub>=25°C unless otherwise noted)**


Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
<b>Static Characteristics</b>						
Drain-Source Breakdown Voltage	<b>V<sub>(BR)DSS</sub></b>	V <sub>GS</sub> = 0V, I <sub>D</sub> = 250μA	20	-	-	V
Zero Gate Voltage Drain Current	<b>I<sub>DSS</sub></b>	V <sub>DS</sub> = 20V, V <sub>GS</sub> = 0V	-	-	1	μA
Gate-Body Leakage current	<b>I<sub>GS</sub></b>	V <sub>DS</sub> = 0V, V <sub>GS</sub> = ±8V	-	-	±10	μA
Gate-Threshold Voltage	<b>V<sub>GS(th)</sub></b>	V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 250μA	0.45	-	1.5	V
Drain-Source on-Resistance <sup>4</sup>	<b>R<sub>DS(on)</sub></b>	V <sub>GS</sub> = 4.5V, I <sub>D</sub> = 2A	9.5	13	15.5	mΩ
		V <sub>GS</sub> = 4.0V, I <sub>D</sub> = 2A	10	13.5	16.5	
		V <sub>GS</sub> = 3.7V, I <sub>D</sub> = 2A	10.5	14	17.5	
		V <sub>GS</sub> = 3.1V, I <sub>D</sub> = 2A	11	15	19	
		V <sub>GS</sub> = 2.5 V, I <sub>D</sub> = 2A	13	17.5	24	
Forward Transconductance <sup>4</sup>	<b>g<sub>fs</sub></b>	V <sub>DS</sub> = 10V, I <sub>D</sub> = 4A	-	17	-	S
<b>Dynamic Characteristics<sup>5</sup></b>						
Input Capacitance	<b>C<sub>iss</sub></b>	V <sub>DS</sub> = 10V, V <sub>GS</sub> = 0V, f = 1MHz	-	730	-	pF
Output Capacitance	<b>C<sub>oss</sub></b>		-	85	-	
Reverse Transfer Capacitance	<b>C<sub>rss</sub></b>		-	75	-	
<b>Switching Characteristics<sup>5</sup></b>						
Total Gate Charge	<b>Q<sub>g</sub></b>	V <sub>GS</sub> = 4.5V, V <sub>DS</sub> = 15V, I <sub>D</sub> = 2A	-	11	-	nC
Gate-Source Charge	<b>Q<sub>gs</sub></b>		-	2.5	-	
Gate-Drain Charge	<b>Q<sub>gd</sub></b>		-	4.5	-	
Turn-on Delay Time	<b>t<sub>d(on)</sub></b>	V <sub>GS</sub> = 4.5V, V <sub>DD</sub> = 15V, R <sub>G</sub> = 3Ω, I <sub>D</sub> = 2A	-	7.5	-	ns
Rise Time	<b>t<sub>r</sub></b>		-	38	-	
Turn-off Delay Time	<b>t<sub>d(off)</sub></b>		-	48.5	-	
Fall Time	<b>t<sub>f</sub></b>		-	15.7	-	
<b>Drain-Source Body Diode Characteristics</b>						
Diode Forward Voltage <sup>4</sup>	<b>V<sub>SD</sub></b>	I <sub>S</sub> = 8A, V <sub>GS</sub> = 0V	-	-	1.2	V
Continuous Source Current	T <sub>A</sub> =25°C	<b>I<sub>S</sub></b>	-	-	8	A

**Notes:**

1. Repetitive rating, pulse width limited by junction temperature T<sub>J(MAX)</sub>=150°C.
2. The EAS data shows Max. rating . The test condition is V<sub>DD</sub>=25V, V<sub>GS</sub>=10V, L=0.1mH, I<sub>AS</sub>=19A.
3. The data tested by surface mounted on a 1 inch<sup>2</sup> FR-4 board with 2OZ copper, The value in any given application depends on the user's specific board design.
4. The data tested by pulsed , pulse width ≤ 300us , duty cycle ≤ 2%.
5. This value is guaranteed by design hence it is not included in the production test.

## Typical Characteristics



**Outline Drawing –DFN2030-6L****Marking Codes**

Part Number	WM02DN080C		
Marking Code		C080N02 = Device Code WWXX XXX= Date Code	

**Package Information**

Qty: 3k/Reel

**CONTACT INFORMATION**

No.1001, Shiwan (7) Road, Pudong District, Shanghai, P.R.China.201207

Tel: 86-21-68969993 Fax: 86-21-50757680 Email: [market@way-on.com](mailto:market@way-on.com)WAYON website: <http://www.way-on.com>

For additional information, please contact your local Sales Representative.

**WAYON**® is registered trademark of Wayon Corporation.

Specifications are subject to change without notice.  
The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.  
Users should verify actual device performance in their specific applications.